

Highline 80/20 1900 | WT - Woven textile

ege

Productdescription



Highline 80/20 1900 | WT - Woven textile



Productdescription

| DESCRIPTION | METHOD | DATA |
|-------------------------------------|------------------------------------|--|
| CONSTRUCTION CHARACTERISTICS | | |
| STRUCTURE | ISO 2424 | Tufted cut pile |
| GAUGE | ISO 2424 | 1/8 |
| PILE MATERIAL | DIR 96/73, 96/74 | 80% wool, 20% polyamide |
| COLORATION | - | Millitron dyed |
| BACKING | ETL | WT - Woven textile |
| DIMENSIONS | ISO 3018 | Approx. 400 cm |
| TOTAL THICKNESS | ISO 1765 | Apr 10,0 mm. 0.39" |
| SURFACE PILE THICKNESS | ISO 1766 | Apr 7,5 mm. |
| TUFTS | ISO 1763 | Apr 167.000 pr.m2 |
| TOTAL CARPET WEIGHT | ISO 8543 | Apr 3.350 g/m2 98.8 oz./yd2 |
| PILE YARN WEIGHT | ETL | 1.900 g/m2 56.05 oz./yd2 |
| SURFACE PILE DENSITY | ISO 8543. | Apr 0,200 g/cm3 |
| BIOCIDAL TREATMENT | Biocidal Product Regulation | Contains preservative to control microbio.deterioration |
| PERFORMANCE CHARACTERISTICS | | |
| PERFORMANCE AREAS | EN 1307 | Class 33 - Commercial - Heavy |
| GUARANTEE | ETL | Contract certificate |
| PERFORMANCE AREAS | Gulvbranchen | Class 33 |
| STATIC CONTROL | ETL | Permanently antistatic |
| BODY WALKING TEST | ISO 6356 | Antistatic |
| ACOU.INSU. FROM IMPACT NOICE | ETL | 29 dB |
| ACOUSTICAL ABSORPTION | ETL | 0,30 aW |
| SUITABILITY UNDERFLOORHEATING | ETL | Apr 0,17 m2K/W |
| LIGHT REFLECTANCE | ETL | Testreport |
| COLOUR FASTNESS TO LIGHT | ISO 105-B02 | >4 |
| | AATCC 16 | 4.0 |
| COLOUR FASTNESS TO RUBBING WET | ISO 105-X12 | >3 |
| | AATCC 165 | 4.5 |
| COLOUR FASTNESS TO RUBBING DRY | ISO 105-X12 | >3-4 |
| | AATCC 165 | 5.0 |
| COLOURFAST. TO WATER PATTERNED | ISO 105-E01 | >4 |
| CLEANING | AATCC 138 | 3.0 |
| COLOUR FAST.OXIDES OF NITROGEN | AATCC 164 | 5.0 |
| OTHER PERFORMANCE TESTS | ASTM D5252 Hexapod | 2.5/2.0 |
| | - | Commercial - Heavy |
| | AATCC 134 Electrostatic propensity | 2,5 kV |

Highline 80/20 1900 | WT - Woven textile



Productdescription

| DESCRIPTION | METHOD | DATA | |
|---------------------------------|--------------------------------|-----------------------------|--------------------------|
| SAFETY & ENVIRONMENT | | | |
| FIRE CLASSIFICATION | BS 6853, NF X 70-100 | Approved | |
| | ASTM E-648 | Class 1 | |
| | ASTM E662 Smoke Density | <450 | |
| | ASTM D2859 Surface Flamm. | Pass | |
| | EN 13501-1 Euroclass | Cfl-s1 | |
| | RUSSIA | Approved | |
| | CE LABELING | EN 14041 | Certified |
| | | CPR | 1021-CPR-012-2/16 |
| | | Declaration of Performance | DOP 1C-WO/PA-WT |
| | | Notified body no. | 1021 |
| Ce Year | | 11 | |
| Content of PCP | | DL | |
| Formaldehyde emission | | NA | |
| Slip resistance | | Class DS | |
| INDOOR CLIMATE | | BASTA | Registered |
| | | Green Label Plus | Approved |
| | Green Label Singapore | Approved | |
| | DCL Attestation of Conformity | Product complies | |
| | METS Report | Pass | |
| | Emissions dans l'air intérieur | A+/A+ | |
| | Indoor Air Comfort Gold | Group 4 | |
| | ABG | ABG-28-01-04-01-2018 | |
| | ENVIRONMENT | Environmental Product Decl. | EPD-EGE-20150202-CBC1-EN |
| | | Cradle To Cradle Certified | Bronze certified |
| Recycled Content, ISO 14021 | | Apr 3,0 % | |
| Recycled Content for LEED | | Apr 2,0 % | |
| LEED | | Qualified | |
| GUIDES | | | |
| INSTALLATION + ADHESIVE GUIDE | DK | Dansk | |
| | N | Norsk | |
| | S | Svensk | |
| | GB | English | |
| | D | Deutsch | |
| | F | Francais | |
| CLEANING, STAIN REMOVAL | DK | Dansk | |
| | N | Norsk | |
| | S | Svensk | |
| | GB | English | |
| | D | Deutsch | |
| | F | Francais | |

Highline 80/20 1900 | WT - Woven textile



Productdescription

| DESCRIPTION | METHOD | DATA |
|-------------------------------------|-----------|-------------------------------|
| MANUFACTURER CHARACTERISTICS | | |
| FACTORY CERTIFICATION | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | ISO 45001 | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |

Productdescription



All carpets are 100% Cradle to Cradle Certified™

We want to leave the right footprint and make sustainability available to everyone.

Cradle to Cradle helps us do exactly that and therefore all of our carpets are Cradle to Cradle Certified™.

With this product certificate, we prove to the world that we do our utmost to keep valuable materials in circulation, cut down on waste and harmful substances, take better care of our scarce resources, sustain the groundwater, reduce CO₂ emissions and ensure social fairness in our operations and value chain.

Ege Carpets is now the no. 1 brand globally in terms of achieving the highest ever number of certifications in under five years so we are now 100% certified.

Cradle to Cradle is the only choice

With our carpets, it is easier than ever before to choose sustainably. You can pick your very own favourite from thousands of colours, patterns, structures and qualities but you only get one option when it comes to sustainability.

Thus, all of our carpets are 100% Cradle to Cradle Certified™ which means that you can leave the people and planet care taking to us, while focusing your own attention on our great selection of designs.

Products from Ege Carpets:

- do not harm people and environment
- have been thoroughly investigated for material health issues
- are produced with renewable energy
- come from a company that works with water stewardship, CO₂ emissions and social fairness
- 100% Cradle to Cradle Certified™